










Standardspülmenge: 6 Liter
 Standard flush: 6 litre
 Volume de chasse standard: 6 litres
 Settaggio di fabbrica: 6 litro
 Standaard spoelwater: 6 liter
 Descarga estándar: 6 litros
 Spłukiwanie standardowe: 6 litrów
 Стандартный смыв: 6 литров




Restwasserhöhe bei 6 Liter > Restwasserhöhe bei 9 Liter
 residual water height at 6 litre > residual water height at 9 litre
 Volume résiduel pour 6 litres > Volume résiduel pour 9 litres

9820670




P +




P =
Druck
Pressure
Presiion
Pressione
Druk
Presión
Ciśnienie
Давление

Default = **P_{max}**

P -




position supérieure =
réglage par défaut



9820337


P +



Ø 46 mm Ø 42 mm Ø 39 mm Ø 36 mm

1120/980 mm: ≈ 115 % ≈ 110 % ≈ 105 % ≈ 100 %*
820 mm: ≈ 115 % ≈ 100 % ≈ 90 % ≈ 80 %*

P -







Ø 34 mm Ø 32 mm Ø 30 mm Ø 28v mm

≈ 95 % ≈ 85 % ≈ 75 % ≈ 65 %*
≈ 80 % ≈ 70 % ≈ 55 % ≈ 45 %*

* Spüldruck / Flushing pressure / Pression de chasse / Pressione di scario / Presión de descarga / ciśnienie spłukiwania / колец давление промывки

Spülung ohne WC-Keramik / Flushing without WC ceramics / Chasse sans cuvette WC / Scarico senza ceramica WC / Spoelen zonder wc-keramiek / Descarga sin cerámica-WC / Spłukiwanie bez ceramiki WC / Смыв без унитаза





SP430 035 00 q












Les réservoirs de chasse homologués NF sont équipés en standard avec un restricteur bleu (diamètre 36 mm), et un réglage du volume de chasse à 6 litres.


TECE



























	Art. Nr.	H Standard	T1 min	T2 min
 O DN 100	9 300 300	1150 (1120 - 1350)	160	210
	9 300 303			
	9 300 309			
	9 300 344			
	9 300 100 (...)			
 O DN 50	9 300 322	980 - 1080	160	210
	9 300 301	820 - 920	160	210
	9 041 306	970 - 1350	160	210
	9 310 000	1150 (1120 - 1350)	140 (115)	210
	9 310 004			
 O DN 50	9 020 033	820 - 1350	140 (115)	210
	9 020 018			
	9 020 034			
	9 320 002			
	9 320 000	1150 (1120 - 1350)	140 (115)	170
 O DN 50	9 320 001			
	9 020 017			
 O DN 50	9 330 000	1150 (1120 - 1350)	140 (115)	210





TECEprofil – WC 1120 mm

